

SPECIFICATION REQUIREMENT
FOR SQ. IN. OF NET FREE AIR
PER LINEAL FT.
(IF APPLICABLE)


RIDGE VENT COVER
(12'-0" (3.65 m) LENGTHS)

.050" (1.27 mm) EXPANDED
METAL SUPPORT SCREEN

8" WIDE (203 mm)
CONCEALED SPLICE PLATE

FASTENERS
(BY OTHERS)

ENDCAPS



STYLE A


ROOF
PITCH

12

FASTENERS
(BY OTHERS)

CONTINUOUS
20 GA. (1.00 mm)
GALV. "Z" BRACKET

DIMENSION
CALCULATED
BY M-E AIRFLOW
SOLUTIONS



STYLE B
(HIGH WALL OR ROOF
PENETRATION SUCH AS AT A
DORMER OR CHIMNEY)

OSB OR
PLYWOOD
(BY OTHERS)

SHINGLED ROOF SHOWN
IF STANDING SEAM CONDION, PLEASE SUPPLY
HEIGHT OF STANDING SEAM

ACTUAL LINEAL
FOOTAGE OF RIDGE

ACTUAL LINEAL
FOOTAGE OF EAVE

COVER:

- | | |
|--|---|
| <input type="checkbox"/> 24 Ga. (.65 mm) Galv. Steel | <input type="checkbox"/> .040" (1.01 mm) Aluminum |
| <input type="checkbox"/> .050" (1.27 mm) Aluminum | <input type="checkbox"/> .063" (1.60 mm) Aluminum |
| <input type="checkbox"/> Other _____ | |

Color: _____

Finish: _____

RIDGE VENT SHINGLED VERSION IS TO BE INSTALLED PER
SPECIFICATIONS AND METAL FLASH INSTALLATION INSTRUCTIONS